

STACK

STACK [TOP] { **COMMAND** *operand1* [*operand2* [(*parameter*)]]... }
{ [**DATA**] [**FORMATTED**] { *operand2* [(*parameter*)]]... }

Operand	Possible Structure					Possible Formats										Referencing Permitted	Dynamic Definition
Operand1	C	S	A	G	N	A										yes	no
Operand2	C	S	A	G	N	A	N	P	I	F	B	D	T	L	G	yes	yes

Related Statements: INPUT | RELEASE

Function

The STACK statement is used to place any of the following into the Natural stack:

- the name of a Natural program or Natural system command to be executed;
- data to be used during the execution of an INPUT statement.

For further information on the stack, see the section Further Programming Aspects of the Natural Programming Guide.

TOP

If you specify TOP, the data/program/command will be placed at the top of the Natural stack. Otherwise, they are placed at the bottom of the stack.

Example:

The following statement causes the content of the variable #FIELD1 to be placed as data on top of the stack:

```
STACK TOP #FIELD1
```

DATA

DATA (which is also the default) causes data to be placed in the stack which are to be used as input data for an INPUT statement.

Delimiter characters or input assign characters contained within the data values will be processed as delimiters. For details on how data from the stack are processed by an INPUT statement, please refer to the description of the INPUT statement.

Example:

The following statements cause the contents of the variables #FIELD1 and #FIELD2 to be placed in the stack:

```
MOVE 'ABC' TO #FIELD1
MOVE 'XYZ' TO #FIELD2
STACK #FIELD1 #FIELD2
```

These variables will be passed as data to the next INPUT statement in the Natural program, using delimiter mode:

```
INPUT #FIELD1 #FIELD2
```

Note:

If operand2 is a time variable (format T), only the time component of the variable content is placed in the stack, but not the date component.

FORMATTED

FORMATTED causes all data to be passed on a field-by-field basis to the next INPUT statement; no key assignments or delimiter characters will be interpreted.

Examples:

The following statements cause "ABC,DEF" to be placed in #FIELD1 and "XYZ" in #FIELD2:

```
MOVE 'ABC,DEF' TO #FIELD1
MOVE 'XYZ'      TO #FIELD2
STACK TOP DATA FORMATTED #FIELD1 #FIELD2
...
INPUT #FIELD1 #FIELD2
```

Assuming the input delimiter character to be the comma (ID=,), the following statements - without the keyword FORMATTED - cause "ABC" to be placed in #FIELD1 and "DEF" in #FIELD2:

```
MOVE 'ABC,DEF' TO #FIELD1
STACK TOP DATA #FIELD1
...
INPUT #FIELD1 #FIELD2
```

COMMAND operand1

To place a command (or program name) in the stack, you specify the keyword **COMMAND** followed by the command (*operand1*). Natural will execute the command instead of displaying the **NEXT** prompt and prompting the user for input.

Example:

The following statement causes the command **RUN** to be placed at the top of the stack. Natural will execute this command at the point where the **NEXT** prompt would normally be issued.

STACK TOP COMMAND 'RUN'

COMMAND operand1 operand2...

Together with a command (*operand1*), you may also place data (*operand2*) in the stack. These data will then be processed by the next **INPUT** statement after the command has been executed.

Data stacked with a command are always stacked unformatted.

Note:

If the data to be stacked include empty alphanumeric fields (i.e., blanks), these blanks will be interpreted as delimiters between values and thus not processed correctly by the corresponding **INPUT** statement. Therefore, if you wish to stack empty alphanumeric fields as data with a command, you have to use two **STACK** statements: one "STACK DATA operand2..." to stack the data, and one "STACK COMMAND operand1" to stack the command.

parameter

If *operand2* is a date variable, you can specify the session parameter **DF** as parameter for this variable. The session parameter **DF** is described in the Natural Reference documentation.

Example

```

/* EXAMPLE 'STKEX1': STACK
/*****
INPUT 'PLEASE SELECT DESIRED FUNCTION:' //
  10X 'LIST FILES (F)' /
  10X 'LIST PROGRAMS (P)' /
  10X 'FUNCTION:' #RSP (A1)
/*****
IF NOT (#RSP = 'F' OR = 'P')
  REINPUT 'PLEASE ENTER A CORRECT FUNCTION'
/*****
IF #RSP = 'F'
  DO STACK TOP COMMAND 'LIST FILES *' STOP DOEND
/*****
IF #RSP = 'P'
  DO STACK TOP COMMAND 'LIST PROGRAMS *' STOP DOEND
/*****
END

```

PLEASE SELECT DESIRED FUNCTION:

LIST FILES (F)
LIST PROGRAMS (P)
FUNCTION: p

```

16:51:17          ***** NATURAL LIST COMMAND *****
USER: TM          LIST
C Name           Pgm. Type   SM S/C Vers Level Userid  Time    Date
- - - - -
SISXXX   Program      S  S   2.1  0000  RJ      12:06  87:03:13
SKPEX1   Program      R  S   2.1  0000  RJ      19:24  87:03:23
SKYEX1   Program      S  S   2.1  0000  RJ      19:02  87:03:23
SRTEX1   Program      R  S   2.1  0000  RJ      10:11  87:03:13
SRTEX1R   Program      R  S   2.1  0000  RJ      09:44  87:03:24
SRTEX1S   Program      S  S   2.1  0000  RJ      09:48  87:03:24
SRTEX2   Program      S  S   2.1  0000  RJ      10:35  87:03:13
STIEX1   Program      S  S   2.1  0000  RJ      19:21  87:03:23
STKEX1   Program      R  S   2.1  0000  RJ      09:54  87:03:24
STKEX1R   Program      R  S   2.1  0000  RJ      10:46  87:03:13
STOEX1   Program      S  S   2.1  0000  RJ      11:28  87:03:13
STOEX1R   Program      R  S   2.1  0000  RJ      10:45  87:03:24
STOEX1S   Program      S  S   2.1  0000  RJ      10:14  87:03:24
STOEX1T   Program      R  S   2.1  0000  RJ      19:35  87:03:24
STOEX1U   Program      R  S   2.1  0000  RJ      19:42  87:03:24

```